



TESTING SUMMARY

TrimLine Dock and Cradle for Panasonic CF33 Tablet
 (AS7.P033.100 | AS7.P033.102 | AS7.P033.110 | AS7.P033.112 | AS7.P033.104)

Test Description	Test Parameters
Vibration: Operational <i>Test date: Oct 2018</i>	MIL-STD-810G, Method 514.6, Procedure 1, Category 4, per Figure 514.6C-1. Test duration is one hour along three mutually orthogonal axes – not simultaneously (6 hours total). <ul style="list-style-type: none"> • Unit is unlocked • Panasonic provided operating conditions • RF connection is also monitored during the test. • Test is monitored to record any breaks in RF connectivity during vibration.
Vibration: Non-Operational <i>Test date: Oct 2018</i>	MIL-STD-810G, Method 514.6, Category 24, per Figure 514.6E-1. Test duration is one hour along three mutually orthogonal axes – not simultaneously (3 hours total). <ul style="list-style-type: none"> • Unit is unlocked
Mechanical Shock Safety: Non-Operational <i>Test date: Oct 2018</i>	MIL-STD-810G, Method 516.6, Procedure 1, 3 positive and 3 negative pulses along three mutually orthogonal axes (6 hours total). <ul style="list-style-type: none"> • 40G, 11ms half sine • Unit is unlocked
Cycle Test: Non-Operational <i>Test date: May 2018</i>	30,000 cycles of the docking connector, latching and locking mechanisms
Shock – Crash Hazard: Non-Operational <i>Test date: June 2018</i>	SAE J1455, Section 4.11.3.5, per Figure 13 <ul style="list-style-type: none"> • Unit is unlocked • Unit is tested in front to back and side to side orientations
Electrostatic Discharge: Operational <i>Test date: July 2018</i>	ISO 10605, Section 8, Table C.2, Category 2 – Direct Air Discharge
EMC Testing <i>Test date: July 2018</i>	<ul style="list-style-type: none"> • FCC Part 15, Subpart B • ICES-003 Issue 6 • CISPR 32/EN 55032:2012/AC:2013 • EN 50498:2010
Electrical Safety Testing <i>Test date: Aug 2018</i>	<ul style="list-style-type: none"> • CSA C22.2 No. 60950-1 • UL 60950-1
Low Temperature: Operational <i>Test date: July 2018</i>	MIL-STD 810G, Method 502.5, Procedure II <ul style="list-style-type: none"> • -10°C Operation, 24-hours
Low Temperature: Storage <i>Test date: July 2018</i>	MIL-STD 810G, Method 502.6, Procedure I <ul style="list-style-type: none"> • -40°C Non-Operational, 72 hours
High Temperature: Operational <i>Test date: July 2018</i>	MIL-STD 810G, Method 501.5, Procedure II, Table 501.5-II, Induced Conditions <ul style="list-style-type: none"> • Five 24-hour cycles, temperature varied from 30°C to 63°C to 30°C

High Temperature: Storage <i>Test date: July 2018</i>	MIL-STD 810G, Method 501.5, Procedure I, Table 501.6-III, Induced Conditions <ul style="list-style-type: none"> • 85°C Non-Operational, 72 hours
Thermal Shock <i>Test date: Oct 2018</i>	MIL-STD 810G, Method 503.5, Procedure I-C <ul style="list-style-type: none"> • Fifty cycles from 85°C to -40°C to 85°C; Dwell Time of 2 hours at each temp.
Humidity <i>Test date: July 2018</i>	MIL-STD 810G, Method 507.5, Procedure II, Aggravated, Table 507.5- IX <ul style="list-style-type: none"> • Ten 24-hour cycles, temperature varied from 30°C to 60°C to 30°C at constant 95% relative humidity.
RoHS Compliance <i>Date: July 2018</i>	EN 50581:2012 RoHS2 Directive 2011/65/EU



Conforms to CSA C22.2 No. 60950-1-07, UL 60950-1
REGULATORY MODEL: AS7.P033.112

www.precisionmounts.com

call us at 1-888-869-7652 | info@precisionmounts.com