



## 6 PORT USB C 3.2 HUB

The 6 Port USB C 3.2 Hub is compatible with a wide range of operating systems including Windows, Linux and MacOS. Features a variety of USB A and USB C ports for connecting peripherals, accessories, and other devices. Mounts using a 1.75" x 5.5" hole pattern with #8 screws and includes USB A to USB B cable for host connection.

### FEATURES

- CNC machined aircraft grade aluminum construction to ensure a lightweight, ultra-rugged solutions
- Black epoxy powder coat finishes provide years of durable, low maintenance performance
- 6 USB ports (USB A and USB C) for connecting multiple peripherals and accessories
- Plug and play functionality for quick deployment with no drivers required
- Compatible with Windows, Linux and MacOS systems for broad integration
- Individual LED indicators per port to show power and USB status during operation
- Overcurrent protection to safeguard connected devices
- Latch locking DC power input to reduce risk of accidental disconnection
- Operating temperature 0°C to 45°C
- Storage temperature -20°C to 70°C
- 5Gbps max data transfer rate
- USB A to USB B cable included
- 1 year limited warranty



### TECHNICAL SPECIFICATIONS

ITEM NO.	HEIGHT	WIDTH	DEPTH	WEIGHT
AS7.U050.016	1.19"	6.13"	2.68"	0.85 lbs

### PORT REPLICATOR

- 4 x Downstream USB A 900mA maximum
- 2 x Downstream USB C 900mA maximum
- 1 x Upstream USB B Input
- 1 x DC IN terminal block +9~30V DC